

PaintFlex® HDPE Boat Anti-Fouling System - 02



You can apply a “Conventional Anti-Fouling paint”
on the PaintFlex® Paint, **DIRECTLY**.

First Paint of Anti-Fouling Paint	Re-paint of Anti-Fouling Paint
HDPE Carbon Black HULL PaintFlex® Classic Grey Conventional Anti-fouling Paint 1. Apply PaintFlex® on the HDPE Carbon Black Board(Hull). (*) 2. Apply a Conventional Anti-Fouling paint on the PaintFlex® paint, Directly.	HDPE Carbon Black HULL PaintFlex® Classic Grey + Conventional Anti-fouling Paint 1. Remove old Conventional Anti-Fouling paint by high pressure washer. 2. Remind: PaintFlex® is resisted washing with high pressure washer. 3. If needs, touch up PaintFlex® on the HDPE Carbon Black Board (Hull). (*) 4. Apply a Conventional Anti-Fouling paint on the PaintFlex® paint, Directly.
(*) PaintFlex® is applied on the Polyethylene directly by Sprey/Brash/Roller. No need heating/ corona/ chemical etching etc... treatment for apply paintFlex®.	



Photo:19/Oct./2023

- ✓ Only re-paint Anti-Fouling Paint end of 2025.
- ✓ Remind: No re-paint PaintFlex® Paint promoter for Anti-Fouling.
- ✓ “NO” re-paint other part of paint.
- ✓ Engine: 1100 hours



Photo: 24/Jun.2026